

Securely manage your schools entryway.

More than a temperature scanner, it adapts to your entryway management needs.

- Securely scan temperatures in less than a second
- 2. Accurately measure temperatures within 0.9 F
- 3. 99% accurate facial recognition without mask
- 4. Reliably detect for a wide variety of mask styles
- 5. Free, unlimited help & training



made with
Qualcom
Technologies

OneScreen GoSafe Prescreen

Easily prequalify visitors based on customizable questions





Advanced Management Console

Al-enabled system that provides ever-smarter insight from your data

SPECIFICATIONS	
Screen	
Size	8.0" IPS LCD screen
Resolution	800x1280
Processor	
СРИ	Qualcomm Snapdragon Octa-Core Processor
Chipset	MSM8953
System	Android 8.1.0
Storage	EMMC 16 GB
Camera	
Resolution	2 million pixels
Туре	Binocular vision wide dynamic camera
Aperture	F2.4
Focusing Distance	19.6"- 60"
White Balance	Auto
Photo Flood Light	LED and IR dual photo fill-In light
Infrared Thermal Imaging Module	
Temperature Detection	Available
Temperature Detection Distance	3.2' (optimal distance 1.6')
Temperature Measurement Accuracy	≤ ±0.9 °F
Temperature Measurement Range	50 °F – 107.6 °F
Thermal Scanner Country Of Origin	Germany
Elevated Temperature Alarm	Supported (temperature alarm value can be set)
Interfaces	
Network Module	Ethernet (RJ-45) and Wireless (Wi-Fi)
Audio	2.5W / 4R speakers
USB	1 USB OTG, 1USB HOST standard A port
Serial Communication	1 RS232 serial port
Relay Output	1 door open signal output

Wiegand	1 Wiegand 26/34 Output	
Upgrade Button	Supports USB boot upgrade button	
Access Control Options on Device		
Mask Detection	Available	
Facial Recognition	Available	
IC Card Based Control	Available	
Reception Desk Configuration	Available	
Additional Software Benefits via Console		
Server-Based Facial Recognition	Available	
OneScreen Prescreen Survey Application	Available	
Badge Printing Application	Available and functional with Brother Printer QL820NB	
Attendance Tracking & Reporting	Available	
Email & SMS Notification	Available	
Call IT / Screen Skills Guru for Support	Available	
Remote Management	Available	
Database supported for facial recognition Support	Up to 2,000 unique users (facial data) with above 99% accuracy	
Storage capacity on device for facial data	Upto 30,000 unique faces and more than 100,000 for storage	
System		
Power	DC 12V	
Operating Temperature	0 °F – 140 °F	
Power Consumption	13.5W Max	
Installation Method	Wall Mount, Table Stand & Floor Stand	
Product Size	10.4" x 4.88"	
Weight	2.64 (lb)	
What's in the Box	OneScreen GoSafe, Power Adapter, User Manual	

March 2021 © All rights reserved.

^{*}Shipping weight excludes accessories. Accessories shipped separately. Specifications are subject to change at any time without notice.